

## Clark Hot 10

Hot water self-contained unit



### Standard equipment

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection



- 6.602.0044 Lance 900 mm with quick connection.



- 3.103.0052 Nozzle type 055



- 4.618.0012 High pressure hose 10 m



## Clark Hot 10

- Hot water self-contained unit
- Electrical start with full engine functions control
- Lombardini diesel engine 15LD400 (air cooling)
- Three ceramic pistons, brass linear pump head with separated bypass valve
- Suction and delivery S/S valves.
- Thermal safety valve on the bypass line
- Max water inlet temperature 40° C.
- Pumpmotor gearbox (1650 RPM).
- Auxiliary belt driven sturdy alternator
- Automatic engine RPM regulator
- Integrated detergent suction with external suction probe
- Pressure regulator.
- Glycerine pressure gauge.
- Unique diesel tank for engine and burner
- Tough steel main frame

### Optional:

- S/S header tank (high pressure chemical)
- Varnished soundproofing steel cover set code 6.608.0014
- Trolley set with inflateable wheels & handles code 6.608.0020

### Technical data:

### Clark Hot 10

Code	8.601.0109
Operat. pressure bar	30±170
l/h	1020
Max water temperature	140° C
RPM pump	1650
Engine type	Lombardini diesel
Engine HP	10